



**Size(L×W×H):**22mm×17mm×2.8mm

**Weight:** 5g

## Features

BDS-3,BDS-2,GPS,GLONASS,Galileo,SBAS and QZSS

100Hz data output\*

GNSS+INS navigation

0.8W power consumption

## Applications



Autonomous  
Driving



UAV



Robotics



Precision  
Agriculture

# K802 GNSS Module

## Easy for Integration

K802 is a 22mm×17mm×2.8mm module with surface-mounted design and is ideal for users to integrate. The power consumption is lower to 0.8w.

## Reliable Performance with Optimized Algorithm

K802 module is embedded with ComNav's latest QUANTUM III SoC chip to provide reliable centimeter positioning accuracy in the most challenging dynamic conditions. The multi-frequency and its ability to track all the current and planned GNSS constellations enables it to receive much more satellite signals.

## Professional Level Applications

K802 module adheres to industrial standard quality specifications and production flow and strict qualification tests, which are performed to meet the standard of automotive industry.

## INS+GNSS Navigation for Continuous Positioning

K802 is designed with an onboard high-precision IMU module for RTK positioning, which can provide continuous and high-quality positioning data with inertial navigation fusion algorithm where GNSS signals are lost.

# K802 GNSS Module

K Series GNSS Module Ver.2024.05.06

## Signal Tracking

GPS	L1C/A, L2P, L2C, L5
BDS	B1I, B2I, B2a, B2b, B3I*
GLONASS	G1, G2*
Galileo	E1, E5b, E5a, E6c*
QZSS	L1C/A, L2C, L5
SBAS	L1C/A, L5
NavIC	L5

## Performance specifications

Cold Start	<20s (Adding Acceleration Capture Mode)
Hot Start (with RTC)	<10s (Typical)
Reacquisition	<1s
RTK Initialization time	<5s (baseline<10km)
Initialization Reliability	>99.9%
Velocity Accuracy	≤0.02m/s (PDOP≤4)
Time Accuracy	20ns
Overload	15g

## Positioning specifications

Single Baseline RTK	8 mm+1 ppm Horizontal 15mm+1 ppm Vertical
Post Processing	2.5 mm+1 ppm Horizontal 5mm+1 ppm Vertical
DGPS	<0.4mRMS
SBAS	1m 3D RMS
Standalone	1.5m 3D RMS

## Communications

UART	x3
SPI	x1
Event Marker input	x1
Pulse Per Second (PPS)output	x1
I <sup>2</sup> C	x1

## Anti-interference

Signal-to-interference rate is up to 50dB

## Data Format

Position data output	-ASCII:NMEA-0183GGA,GSA,GSV,RMC, HDT,ZDA,VTG,GST,LL;PTNL,PJK;PTNL, AVR;PTNL,GGK ^-ComNav Binary -Position data output rate:1 Hz,2Hz,5 Hz, 10Hz,20Hz,50Hz,100Hz(optional)
Corrections data	RTCM2.X,3.X,CMR(GPS only),CMR+(GPS only)

## Antenna Interface

Impedance Matching	50 Ω
LNA Power External	+3.3V~+5.0V±5%VDC
LNA Gain	20~40dB

## Physical

Size(L×W×H)	22mm×17mm×2.8mm
Weight	5g

## Environmental

Operating Temperature	-40C~+85C
storage Temperature	-55C~+95C

## Electrica

Voltage	+3.3V±5%DC
Power Consumption	0.8W (Ant-interference off) Set anti-interference on consumes more about 0.2W

\*\*\*upgradeable  
1.R(meter) is the length of two GNSS antennas.